Sav9D
DC CCTV Power Supply

Rev. DSSAV9D - 12162011

Overview

Sav9D

Altronix Sav9D Power Supply provides 12VDC distributed via nine (9) Class 2 Rated PTC protected power limited outputs for powering surveillance cameras.

Specifications

Input:
- 115VAC 60Hz, 1.5 amp /230VAC 50Hz, 0.75 amp.

Output:
- 12VDC @ 5 amp total output current *(0.55 amp per device, 2.5 amp max.)*.
- Nine (9) Class 2 Rated PTC protected power limited outputs.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.

Electrical:
- Operating temperature: 0º C to 49º C ambient.
- 23 BTU/Hr.
- System AC input VA requirement: 172.5VA.

Mechanical:
- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 8.5” (215.9mm) x 7.5” (190.5mm) x 3.5” (88.9mm)
- Product weight (approx.): 4.6 lbs. (2.08 kg.).
- Shipping weight (approx.): 5.1 lbs. (2.31 kg.).

Features:
- Nine (9) power LEDs.
- Power ON/OFF switch.
- Field installable 3-wire line cord with integral strain relief.
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions *(H x W x D) (approximate)*:

8.5” (215.9mm) x 7.5” (190.5mm) x 3.5” (88.9mm)